

Vended Specifications

MODEL			HXC-22		HXC-35		HXC-50		HXC-65		HXC-85		HXC-110	
UNITS	METRIC	US	METRIC	US	METRIC	US	METRIC	US	METRIC	US	METRIC	US	METRIC	US
CAPACITY														
Loading Factor 1:10	kg	LBS	8.24	18.2	13.5	29.7	19.6	43.2	27.5	60.6	36	79.3	45.4	100
Loading Factor 1:13	kg	LBS	6.34	14	10.4	22.9	15.7	34.6	21.2	47.7	27.7	61	34.9	76.9
OVERALL DIMENSIONS														
A-Width	mm	Inch	660	26	770	30.3	770	30.3	876	34.5	1051	41.4	1051	41.4
B-Depth	mm	Inch	864	34	990	39	1092	43	1168	46	1167	46	1394	55
C-Height	mm	Inch	1028	40.5	1130	44.5	1226	48.3	1334	52.5	1591	62.6	1591	62.6
WASH CYLINDER														
Diameter	mm	Inch	526	20.7	610	24	681	26.8	790	31.1	920	36.2	920	36.2
Depth	mm	Inch	379	14.9	462	18.2	539	21.2	561	22	544	21.3	683	26.9
Volume	liters	cu.ft	82.4	2.91	135	4.77	196	6.93	275	7.71	360	12.7	454	16.1
MOTOR														
Size	kW	HP	0.76	1	1.5	2	2.2	3	3	4	5.5	7.5	7.5	10
CYLINDER SPEED PROGRAMMABLE														
Wash	rpm	G	52	0.8	49	0.8	46	0.8	43	0.8	40	0.8	39.5	0.8
Distribution	rpm	G	100	3	94	3	89	3	82	3	76	3	76	3
Extract maximum	rpm	G	818	200	760	200	726	200	673	200	623	200	622	200
DOOR OPENING														
Door opening diameter	mm	Inch	381	15	418	16.5	483	19	508	20	651	25.6	668	26.3
Height to bottom of door	mm	Inch	324	12.8	349	13.4	401	16	422	16.6	569	22.4	582	22.9
DRAIN SYSTEM														
Drain outlet size	mm	Inch	51	2	51	2	51	2	76.2	3	76.2	3	76.2	3
Number of drains	Standard	Standard	1	1	1	1	1	1	1	1	1	1	1	1
STEAM INLET														
Connection size	DN	NPT	13	1/2	13	1/2	13	1/2	13	1/2	20	3/4	20	3/4
ELECTRICAL HEATING														
Heating element size	kW	kW	6	6	9	9	12	12	18	18	18	18	24	24
WATER INLETS														
Connection size	DN	NPT	20	3/4	20	3/4	20	3/4	20	3/4	20	3/4	20	3/4
Numbers of inlets	Standard	Optional	2	3	2	3	2	3	2	3	2	3	2	3
CHEMICAL SYSTEM														
Number of dry chemicals	Standard	Standard	2	2	2	2	2	2	2	2	2	2	2	2
Number of liquid chemicals	Standard	Standard	2	2	2	2	2	2	2	2	2	2	2	2
External liquid connection	Standard	Standard	8	8	8	8	8	8	8	8	8	8	8	8
WEIGHT & SHIPPING INFORMATION														
Net weight	kg	lbs	199	439	288	635	345	760	429	944	TBA	TBA	TBA	TBA
Shipping weight	kg	lbs	213	470	304	670	360	795	450	990	TBA	TBA	TBA	TBA
Shipping size: Width-Depth-Height	cm	inch	71-96-121	28-38-48	81-109-132	32-43-52	84-119-140	33-47-55	94-134-146	37-53-57.5	TBA	TBA	TBA	TBA
ELECTRICAL SERVICE														
120VAC, 50HZ, 1PH	Amp	Breaker	TBA	TBA	TBA	TBA	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
208-240VAC, 50-60HZ, 1PH	Amp	Breaker	6	15	8.1	15	5.1	15	16.1	20	22	30	31	40
208-240VAC, 50/60HZ, 3PH	Amp	Breaker	3.4	15	3.6	15	4.7	15	7.4	15	12.7	20	18	30
380-460VAC, 50/60HZ, 3PH	Amp	Breaker	1.7	15	1.8	15	2.3	15	3.5	15	6.3	15	9	15
208-240VAC, 50/60HZ, 3PH EL Heat	Amp	Breaker	24	30	26	30	48	60	52	60	75	80	78	80
380-460VAC, 50/60HZ, 3PH EL Heat	Amp	Breaker	13	15	14	15	24	30	26	30	38	40	39	40

Specifications subject to change without notice.



B&C Technologies
 Panama City Beach, FL
 850-249-2222
www.bandctech.com
sales@bandctech.com

60/36 Warranty



60 Months: Bearings, Bearing Housing, Frame, Shaft, Cylinder & Shell
36 Months: All other non wear parts

